

1114L

Tubular Lower A-Arms 78-88 Chevy G-Body

Thank you for your purchase from our new line of G-Body parts.
Please call us at (877) 4NO - ROLL if you have any questions
regarding the service or installation of your Hotchkis products. Visit us online @ www.hotchkis.net

Before You Start:

Please read the entire manual before starting.

1. Raise Vehicle

Raise the vehicle and put it up on jack stands. You may also use a 2-post or 4-post lift.

2. Remove the Front Sway Bar End links

Disconnect the sway bar from each lower A-Arm by removing the sway bar end links.



3. Remove the wheels

Remove both front wheels

4. Undo the Top Shock Mount

Using a combination of wrenches and/or allen keys and remove the top shock mounting nut. Save all shock bushings and hardware for reinstallation.



5. Undo the Bottom Shock Mount

Remove the 2 bolts that secure the bottom shock mount and remove the shock from the vehicle. Keep all bushings and hardware for reinstallation.



6. Disconnect the Outer Tie Rod Ends

Locate the outer tie rod end and remove the cotter pin using a pair of dikes. Use a 11/16" wrench to unfasten the tie rod end castle nut. Hit the steering arm with a hammer to knock the tapered stud out. Allow the tie rod to hang down.




7. Loosen Lower Ball Joint Nut

Locate the lower ball joint nut near the outboard end of the a-arm and remove the cotter pin using a pair of dikes. Use a 7/8" wrench to loosen the castle nut. Do not completely remove this nut! Leave 3 or 4 threads left on the nut.



8. Break Loose the Lower Ball Joint Stud

Using your trusty hammer, hit the spindle until the stud pops loose. The castle nut is there to keep the spring from launching the lower a-arm down.



9. Loosen Inboard A-Arm Bolts

Loosen but **do not** remove the 2 inboard a-arm bolts.

10. Disconnecting the Lower Ball Joint Completely

Place a jack underneath the lower a-arm you are working on and jack the arm up until you start to see the ball joint castle nut start to move up. Remove the ball joint castle nut.



11. Relieving Tension on the Spring

Slowly lower the jack to relieve the tension in the spring. If you are removing OEM springs, you must be extra careful since this type of longer spring has more pre-load.



12. Remove the spring

Once you have lowered the a-arm as far as possible, carefully remove the spring.



13. Remove Stock Lower A-Arm

Fully remove the 2 inboard bolts and remove the stock a-arms.

14. Install Pad Spacer and Lower Spring Isolator

Install the $\frac{1}{4}$ " spacer and the lower spring Isolator onto the Hotchkis a-arm. At this time, do not worry about the index clocking of the isolator. With the $\frac{1}{4}$ " spacer, there is no ride height changes from stock. In some cases, it is necessary to raise or lower the driver or passenger side to getting uniform ride height. If you need to lower or raise the vehicle you can order more $\frac{1}{4}$ " spacers from Hotchkis directly.



Possible Combinations:

No Spacer	= $\frac{1}{2}$ " Lower than Stock Arm
$\frac{1}{4}$ " Spacer	= Same as Stock Arm (Default Setting)
$\frac{1}{4}$ " + $\frac{1}{4}$ " Spacer	= $\frac{1}{2}$ " Higher than Stock Arm

15. Reinstall the Hotchkis A-Arm

Install the a-arm in the same manner as removal. Start with the inboard bolts to the subframe. Fully tighten the inboard bolts at this time.



16. Indexing the Spring (Mock Up)

With the a-arm hanging down, grab the coil spring and place the up into the upper pocket. Some car models will need to be clocked at a certain angle to match up with the index. Use some “white out” and mark the frame and the coil to give you a guide when you are ready to install it for real. If your car does not have the upper indexing, then you can skip this step.




17. Install the Spring

Rotate the a-arm up and place a jack underneath. Place the spring up into the upper pocket and index it using your white out guide. Clock the a-arm isolator so the end of the coil matches up with the index of the isolator. Slowly jack the arm up while pushing the bottom half of the spring inboard into the isolator pocket. This step will be easy with aftermarket lowering springs and difficult with OEM stock springs. For OEM stock springs, you may need to use a series of pry bars to pop the bottom end into the pocket.



Once the bottom is popped in, line up the lower ball joint stud with the bottom of the spindle. Continue to jack the a-arm up and insert the ball joint stud into the spindle. Once the stud is in all the way, install the supplied castle nut. Fully tighten this nut and install the new cotter pin. Once the castle nut is fully fastened, you may release the jack and relieve the pressure on the a-arm.





18. Reinstall the Steering Tie Rod

Reinstall the steering tie rod in the same manner as removal. Don't forget to install the cotter pin.



19. Reinstall the Shock

Reinstall the shocks in the same manner as removal.



21. Install the Sway Bar End links

Attach sway bar to the control arm with the included end links.



Note: 1104 shown

22. Grease the Ball Joints

Grease all of the ball joints

9. Align Your Car

You must get your car aligned by a professional after you install your Hotchkis A-Arms.

More Products for Your G-Body!

1114U

Tubular Upper Trailing Arms

1401

Trailing Arm Braces

1601

Tie Rod Sleeves

1902

1" Lowering Sport Coil Springs

2281

Front & Rear Sport Sway Bar Set

1802A

Upper & Lower Trailing Arms

79010001

Front & Rear HPS 1000 Bilstein Shocks

80009 (Small Block)

Total Vehicle System (TVS) Kit

Includes 1601, 2281, 1802A, 1902

Please visit our website for more information.

www.hotchkis.net

Hotchkis Performance LLC

Return Policy & Limited Warranty

Effective December 1, 2010 all Hotchkis products must be registered to qualify for warranty at www.hotchkis.net or via the mail-in warranty card, included with the product, within 30 days of the original purchase date.

IMPORTANT: This warranty supersedes all other warranties included with this product.

Return Policy

We want you to be completely satisfied with your Hotchkis Performance product. For products, presenting signs of shipping damage please contact the freight carrier immediately. All our products are guaranteed to be free from manufacturer's defects. If your order arrives with a manufacture defect, please contact our Customer Service Department at (562) 907-7757. You will be assigned a Returned Goods Authorization Number (RGA). The package you return must show the RGA on the outside of the package, include the original invoice and be shipped prepaid to our facility. The product has to be unused and in its original packaging materials. Exchanges or refunds made after 30 days will be subject to a 20% restocking charge. **If you purchased your Hotchkis Performance product from an authorized dealer, you are still covered by this return policy. All returns however, should be made to your dealer, not to Hotchkis Performance directly.**

Limited Warranty

Hotchkis Performance offers a Limited Warranty against defects in materials and workmanship for the term of 36 months (3 years) from the date of purchase of this product. This Warranty only applies to the original retail purchaser who retains ownership of the vehicle on which the product was originally installed. If the product is determined to be defective, Hotchkis Performance will repair, replace or refund the purchase price of the defective product at Hotchkis Performance's sole discretion, which shall fully satisfy and discharge any and all warranty claims. Any repaired or replaced product will be returned to the sender excluding the cost of freight. **Products must be registered to qualify for warranty at www.hotchkis.net or via the mail-in warranty card, included with the product, within 30 days of the original purchase date.**

Exclusions from Warranty

Items offered but not manufactured by Hotchkis Performance are warranted according to the manufacturer's terms and are not covered by this limited warranty. Hotchkis Performance shall not be responsible for any labor, removal, installation, re-installation or maintenance costs. This warranty does not cover the cosmetic finish or plating of any product or any normal wear and tear to any product including, but not limited to bushings, brackets, end-links, hardware, steering components, shocks or springs. In addition, this warranty does not apply to any products that have been:

- **Improperly installed or installed by someone other than a qualified, licensed auto mechanic experienced in the installation and removal of suspension products;**
- **Improperly serviced, misused, or modified, altered or subjected to abuse, negligence, accident or collision;**
- **Installed in any vehicle that has been modified;**
- **Installed on any vehicle that has carried loads in excess of automobile manufacturer suggested weight limits; or**
- **Installed on any vehicle that has been subject to abnormal or excessive use, including rallying, racing, or racing-type activities or off-road use.**

Limitation of Warranty

This limited warranty is the entire and only warranty for the products and may not be modified or supplemented by any other person or company in any form. Any description of the products, by anyone, is for the sole purpose of identifying them and is not part of the basis of the bargain, and does not constitute a warranty that the products will conform to that description. The statements of any salesperson do not constitute part of this limited warranty and cannot be relied upon as a warranty.

THERE ARE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. ANY IMPLIED WARRANTIES ARE DISCLAIMED TO THE FULLEST EXTENT PERMITTED BY LAW. THIS WARRANTY DOES NOT COVER CONSEQUENTIAL DAMAGES, LOSS OF TIME OR REVENUES,

INCONVENIENCE, LOSS OF USE OF THE VEHICLE, DAMAGE TO THE VEHICLE OR COMPONENTS OF THE VEHICLE, ANY OTHER TYPE OF CONSEQUENTIAL DAMAGES, OR OTHER INCIDENTAL OR INDIRECT DAMAGES. HOTCHKIS' MAXIMUM LIABILITY UNDER THIS WARRANTY SHALL IN NO EVENT EXCEED THE PURCHASE PRICE OF THE PRODUCT. Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages and in such states the above limitations or exclusions may not apply. This limited warranty gives the purchaser specific legal rights and the purchaser may have other rights that may vary from state to state.

Technical Information

Hotchkis Performance makes every effort to ensure that you are provided with the most accurate and up-to-date technical information. However, all technical information is approximate and may vary upon application. Additional suspension components may be needed in some applications, depending upon the make, model, engine and chassis of the vehicle. Hotchkis Performance is not responsible for any consequences resulting from manufacturer's technical mid-year changes. Hotchkis Performance products should only be installed by a qualified, licensed auto mechanic experienced in the installation of such products.

Warranty Claim Procedure:

The answer to ALL the following questions should be YES before making a warranty claim:

- Did you register the product at www.hotchkis.net or via the mail-in warranty card within 30 days of purchase?
- Is the product appropriate to your application?
- Did you carefully and thoroughly read the instructions provided along with the product?
- Do you have the original invoice or sales receipt?
- Is the return date within 36 months from the purchase date?
- Are you the original purchaser?
- Was the product properly installed by a qualified, licensed auto mechanic?
- Has the product been installed on the original vehicle on which it was installed at all times?
- Is the product unmodified and clean?
- Is the reason for return a legitimate product defect?

If the answer to all these questions is YES, please contact our Customer Service Department at (562) 907-7757. You will be given a Returned Goods Authorization Number (RGA) valid for 60 days. You will also be asked to ship the product prepaid to our facility. All shipments MUST be (i) prepaid, (ii) include the original invoice or sales receipt, (iii) show the RGA on the outside of the package and (iv) include your name, address, make and model of the vehicle, and a brief description of the claimed defect, including the circumstances under which the defect occurred. If the warranty claim is deemed valid then Hotchkis will estimate shipping costs to return the repaired or replacement part and contact you for payment. Hotchkis's Limited warranty requires that any repaired or replaced product will be returned to the sender excluding the cost of freight. Warranty related inquiries should be sent to the following address:

HOTCHKIS PERFORMANCE, LLC
C/O CUSTOMER SERVICE
8633 Sorensen Avenue
SANTA FE SPRINGS, CA 90670

Hotchkis Performance will not accept product returns without the RGA number, receipt and the information described above. C.O.D. or collect shipments will be refused. Once the returns are received at Hotchkis Performance, we will evaluate the products, verify the sales receipt, and investigate the warranty claim. Any repaired or replaced product will be returned to the sender.

Effective December 1, 2010. This return policy and limited warranty supersedes all previous policy and warranty statements. Policies and warranties are subject to change without notice. Hotchkis Performance is not responsible for printing errors.